


RO3156A-2

**868.95 MHz
SAW Resonator**



SM5035-4

- **Designed for European 868.95 MHz SRD Transmitters**
- **Very Low Series Resistance**
- **Quartz Stability**
- **Surface-mount Ceramic Case**
- **Complies with Directive 2002/95/EC (RoHS)**
- **Tape and Reel Standard per ANSI/EIA-481**
- **Moisture Sensitivity Level: 1**
- **AEC-Q200 Qualified**

The RO3156A-2 is a one-port surface-acoustic-wave (SAW) resonator packaged in a surface-mount ceramic case. It provides reliable, fundamental-mode quartz frequency stabilization of fixed-frequency transmitters operating at 868.95 MHz. The RO3156A-2 is designed specifically for SRD transmitters operating in Europe under ETSI EN 300 220-2.

Absolute Maximum Ratings

| Rating | Value | Units |
|--|------------|-------|
| CW RF Power Dissipation | +5 | dBm |
| DC Voltage Between Terminals | ±30 | VDC |
| Case Temperature | -40 to +85 | °C |
| Soldering Temperature, 10 seconds / 5 cycles maximum | 260 | °C |

Electrical Characteristics


| Characteristic | Sym | Notes | Minimum | Typical | Maximum | Units | |
|--|--------------------------------------|-------|---------|---------|---------|---------------------|-----|
| Frequency, +25 °C | f_C | | 868.850 | | 869.050 | MHz | |
| Tolerance from 868.95 MHz | Δf_C | | | | ±100 | | kHz |
| Insertion Loss | IL | | | 1.2 | 2.0 | | |
| Quality Factor | Unloaded Q | Q_U | | 6200 | | | |
| | 50 Ω Loaded Q | Q_L | | 850 | | | |
| Temperature Stability | Turnover Temperature | T_O | 10 | 25 | 40 | °C | |
| | Turnover Frequency | f_O | | f_C | | kHz | |
| | Frequency Temperature Coefficient | FTC | | 0.032 | | ppm/°C ² | |
| Frequency Aging | Absolute Value during the First Year | fA | | <±10 | | ppm/yr | |
| DC Insulation Resistance between Any Two Terminals | | | 1.0 | | | M Ω | |
| RF Equivalent RLC Model | Motional Resistance | R_M | | 14.5 | | Ω | |
| | Motional Inductance | L_M | | 18.0 | | μ H | |
| | Motional Capacitance | C_M | | 2.0 | | fF | |
| | Shunt Static Capacitance | C_O | | 2.1 | | pF | |
| Test Fixture Shunt Inductance | L_{TEST} | | | 15.8 | | nH | |
| Lid Symbolization: YY = Year, WW = Week, S = Shift | 828, <u>YYWWS</u> | | | | | | |

 **CAUTION: Electrostatic Sensitive Device. Observe precautions for handling.**
NOTES:


1. The design, manufacturing process, and specifications of this device are subject to change.
2. US or International patents may apply.
3. RoHS compliant from the first date of manufacture.

Electrical Connections

The SAW resonator is bidirectional and may be installed with either orientation. The two terminals are interchangeable and unnumbered. The callout NC indicates no internal connection. The NC pads assist with mechanical positioning and stability. External grounding of the NC pads is recommended to help reduce parasitic capacitance in the circuit.




Equivalent RLC Model




Typical Test Circuit

The test circuit inductor, L_{TEST} , is tuned to resonate with the static capacitance, C_0 , at F_C .

ELECTRICAL TEST




POWER TEST




Temperature Characteristics

The curve shown on the right accounts for resonator contribution only and does not include LC component temperature contributions.





Case




Typical Application Circuits

Typical Low-Power Transmitter Application



PCB Footprint

Typical Local Oscillator Applications



| Dimensions | Millimeters | | | Inches | | |
|------------|-------------|------|------|--------|-------|-------|
| | Min | Nom | Max | Min | Nom | Max |
| A | 4.87 | 5.00 | 5.13 | 0.191 | 0.196 | 0.201 |
| B | 3.37 | 3.50 | 3.63 | 0.132 | 0.137 | 0.142 |
| C | 1.45 | 1.53 | 1.60 | 0.057 | 0.060 | 0.062 |
| D | 1.35 | 1.43 | 1.50 | 0.040 | 0.057 | 0.059 |
| E | 0.67 | 0.80 | 0.93 | 0.026 | 0.031 | 0.036 |
| F | 0.37 | 0.50 | 0.63 | 0.014 | 0.019 | 0.024 |
| G | 1.07 | 1.20 | 1.33 | 0.042 | 0.047 | 0.052 |

Recommended Reflow Profile

1. Preheating shall be fixed at 150~180°C for 60~90 seconds.
2. Ascending time to preheating temperature 150°C shall be 30 seconds min.
3. Heating shall be fixed at 220°C for 50~80 seconds and at 260°C +0/-5°C peak (10 seconds).
4. Time: 5 times maximum.

